EXTERNAL DOORS

Windsor Inline DDA Lever Lever



Features

- Solid die cast Zinc construction with heavy duty spring cassette Sturdy feel and consistent 90 degree lever return
- Sculpted extended ergonomic lever and low friction nylon bush Easy to grip and smooth action and low operating forces required
- Supplied with screw and spindle pack to suit 44mm composite doors Everything needed for installation included
- Colour coordinated screw heads Perfectly matching hardware, even down to the smallest details
- Baseplate in common with all Windsor handles Same routing detail regardless of product variant chosen
- · Wide and compact backplate with screws in close proximity To suit cylinder guards, accommodate larger cylinder preparation and combat lever attacks
- Supplied with care instructions Helps the homeowner to keep the hardware in optimal condition
- Supplied fully assembled Simple and quick installation, no need to fit springs or lever
- Each part packaged in a separate chamber, but supplied as a set No scratching of parts during transit
- · Ample lever-to-door surface clearance and available in a wide range of contrasting colours

Compliant with Document M of The Disability Discrimination Act (DDA)



Hardex



Hardex Gold



Hardex Bronze



Antique Black














EXTERNAL DOORS

Windsor Inline DDA Lever Lever

Ordering Details		
Product		
Windsor Inline DDA Lever Lever		
Finish	Part No.	
Hardex Chrome	1F301	
Hardex Bronze	1F303	
Hardex Gold	1F305	
Antique Black	1F306	
White	1F300	

Technical Information		
Corrosion resistance Meets the requirements of BS EN 1670:2007 Grade 5 (480 hours)		
Operation Endurance tested in excess of 20	00,000 cycles	
Performance Tested to meet the requirement	s of PAS 24 as part of a compliant door set	
Material Specificatio	n	
Handle Grip and Backplate:	High quality Zinc for all finishes	
Coatings:	Hardex Chrome, Hardex Bronze, Hardex Gold, Antique Black and White	
Spindle / Screws:	Machine screws with colour coordinated heads for handle. 44mm composite doors (1 x 8mm x 110mm spindle and 2 x M5 x 55mm screws) Spindle and screw pack for 60-70mm door profiles available on request, please contact our sales office	
Cylinder:	Euro Cylinder, 92mm PZ	

155 20 Extended Lever 92 206 143. 28



Maintenance

For continued protection of the quality finish and appearance, we advise routine cleaning of all our external hardware. We recommend wiping it with a clean cloth soaked in warm water and mild detergent every month. Please refrain from using heavy-duty cleaners, containing Chlorine or Potassium. Moving parts should also be lightly lubricated using a light non-acidic mineral oil (e.g., "3 in 1") at least twice per year. The product may need to be adjusted and fixings tightened to ensure a satisfactory operation. This procedure is particularly essential if products are used within a 25-mile radius of coastal areas or close proximity to building sites or large industrial areas, where more frequent cleaning may be required to prevent the accumulation of corrosive contaminants.

Packaging

Handles

Individually bagged with screws, spindle and care instructions. 15 handles in an outer box.

All dimensions are in mm and are nominal. $\label{prop:pababababa} \mbox{{\it Fab}\&Fix reserves the right to change specification without notice}$ It is the responsibility of the door manufacturer to ensure that the finished product meets any required safety and performance specification.