CASENENT HINDONS

Additional Economy Window Locks



Metlock



Transom Lock

Features

Metlock

- Utilises a high tensile steel bolt to prevent the handle from moving
- The steel construction is operated by a standard key
- Suitable for most Cockspur handles on metal windows

Transom Lock

- Clamps the window stay to the fixed peg on metal transom windows
- Fully removable to allow normal window opening

Locking Window Catch

- Manufactured from steel and brass to hold the window tight against
- Operated by a threaded peg and key operated locknut
- Suitable for most timber windows and small doors
- Wedged packing plates are included for tapered frames

- Suitable for most stays, with or without holes for through-pegs
- Ideal for most timber casement windows
- Fitted with a tamper resistant spring loaded locking system
- Key operated



Locking Window Catch



Staylock









Additional Economy Window Locks

Part No. Retail Boxed Version
829-17
825-17
580-56
Čey Control of the Co
828-57
820-37
820-57

Packaging

Cardboard packaging with euro hooks. 2 per retail box, 5 retail boxes per outer box. 0.14Kg per item, 0.7Kg per outer box.

Cardboard packaging with euro hooks. 1 per retail box, 5 retail boxes per outer box. 0.13Kg per item, 0.65Kg per outer box.

Locking Window Catch

Cardboard packaging with euro hooks. 1 per retail box, 5 retail boxes per outer box. 0.13Kg per item, 0.65Kg per outer box.


Cardboard packaging with euro hooks. 1 per retail box, 5 retail boxes per outer box. 0.13Kg per item, 0.65Kg per outer box.

Maintenance


The pivot point should be lightly lubricated twice a year and the surface cleaned with a soft cloth to remove any dust or grime. The product should be periodically adjusted and the fixings tightened to ensure a satisfactory




Metlock




Transom Lock



Locking Window Catch





All dimensions are in mm. ERA reserves the right to change specification without notice. It is the responsibility of the window manufacturer to ensure that the finished product meets any required safety and performance specification